

General	
Standards	ITU G.992.1 (G.dmt) ITU G.992.2 (G.lite) ITU G.994.1 (G.Hs) ANSI T1.413 (Issue 2)
Protocol:	TCP/IP
Data Transfer Rate	G.dmt full rate: Downstream up to 8 Mbps Upstream up to 640 Kbps
Media Interface Exchange	RJ-12 port ADSL telephone line connection RJ-45 port for 10BaseT Ethernet connection

Physical and Environmental	
DC inputs	Input: 240V AC 50Hz 24W
Power Adapter	Output: 9V AC 1000mA
Power Consumption	10 Watts (Max)
Operating Temperature	0° to 50° C (32° - 122° F)
Humidity	5 to 95% (non-condensing)
Dimensions	180mm x 140mm x 30mm
Weight	455gm (1 lb.)
EMI:	FCC Class B, CE Class B
Safety	CSA International

## Table of Contents

<b>1.0</b>	<b>INTRODUCTION</b>	<b>2</b>
<b>2.0</b>	<b>USING THE SELF-INSTALLATION CD</b>	<b>2</b>
<b>3.0</b>	<b>INSTALLING YOUR MODEM</b>	<b>3</b>
3.1.1	INSTALLING FILTERS	3
3.1.2	CONNECTING THE CABLES	4
3.1.3	STARTING YOUR MODEM	4
<b>4.0</b>	<b>MANUAL MODEM CONFIGURATION</b>	<b>5</b>
4.1	PC SETTINGS	6
4.1.1	PC SETTINGS FOR WINDOWS 98/ME	6
4.1.2	PC SETTINGS FOR WINDOWS 2000	9
4.1.3	PC SETTINGS FOR WINDOWS XP	12
4.2	CONFIGURE YOUR MODEM	16
<b>5.0</b>	<b>QUICK DIAGNOSTICS</b>	<b>18</b>
<b>6.0</b>	<b>CUSTOMER SUPPORT</b>	<b>18</b>
<b>7.0</b>	<b>TECHNICAL SPECIFICATIONS</b>	<b>19</b>

Version 1.0

© Optus Administration Oct 2003