



DFL-1000

“Rack-mount firewall with complete virus scanning, access control, intruder protection, remote VPN connection and DMZ functions for company networks.”

Network Secure Firewall for Workgroups

The DFL-1000 is a cost-effective firewall that provides comprehensive network protection, performance and easy installation. A hardware device that is much easier to install and more effective than software-based firewalls, the DFL-1000 offers an ideal protection for SMB or even SOHO, with plug-and-play connection, complete security against outside intruders, Virtual Private Network (VPN) support through data encryption and authentication, and easy administration.

Complete Security

Your office is connected to the outside world through the Internet. It is easy for hackers to intrude your databases to steal or destroy data. The DFL-1000 provides a wide range of protection against outside attacks, plus comprehensive security that includes user authentication, scheduled policies and Virtual Server Mapping. The DFL-1000 provides NAT translation of IP addresses from the internal private network to the public IP network.

Content Filtering & Virus Scanning

The DFL-1000 provides filtering of potentially malicious codes embedded in web pages to remove Active objects, java, JavaScript and other potential threats. It provides virus scanning for all incoming and outgoing email and attachments, plus virus check for Web plug-ins and downloaded Web content.

Easy Installation

All you need to do is connect the network cables. To the outside world, you hook the RJ-45 plug to your DSL/cable modem, Internet gateway or router. To your office, you plug in another RJ-45 jack to your network switch or hub. The DMZ port connects to an independent hub or switch for the DMZ network. The DFL-1000 provides CPU, system memory and embedded software, all ready to run.

Access Control

Administration access can be controlled such that the DFL-1000 can be administered from the protected internal network

or the external public Internet. The DFL-1000 supports an internal/External (RADIUS) database for authenticating user access to various services. It maps public IP addresses to information servers on the internal network to allow public access. It also prevents access to particular web sites, using powerful pattern matching to block access to URLs.

Scheduled Policies

Firewall policies may be scheduled for different times of the day/week/month and for one time use or recurring.

LAN-to-LAN VPN Connection

The DFL-1000 supports VPN functions including IPSec, ESP security in tunnel mode, LAN to-LAN and mobile remote access.

Hardware Acceleration

The DFL-1000 uses a special design ASIC to perform VPN encryption and decryption. It off-loads CPU loading through hardware-based acceleration.

Management

The DFL-1000 supports web-based management using a secure SSL connection from a remote terminal either on the internal corporate network or even from an external remote site. The DFL-1000 can also be administered on-site using its RS-232 serial connection.

Key Features

- Easy to install, easy to manage
- Web-based management and software updated via browser
- Intruders prevention through MAC Address bind with IP
- Secure system management via VPN Tunnel on any interface
- Triple-DES data encryption
- Anti-virus scanning

DFL-1000

Technical Specifications

General Services

- ftp
- http
- NAT

Authentication

- HMAC MD5 or HMAC SHA-1 Authentication/data integrity

Key Exchange

Automatic IKE based on Pre-Shared Key

Attack Protection Provided

- IP Source Routing
- IP Spoofing
- SYN flood attack
- ICMP flood
- UDP flood
- Land attack
- Address sweep attack
- Tear drop attack
- Winnuke attack
- Port Scan attack
- Ping of Death

Hardware Specifications

Processor

300MHz

System Memory

On board 256MB

Flash Memory

64MB Compact Flash Card

Network Interface

3 10/100Mbps ports (1 Internal, 1 External, 1 DMZ)

LED Indicators

- Power
- Status
- Interface link and activity

Software Specifications

Dedicated VPN Tunnels

300

Concurrent Sessions

25,000

User Authentication Support

RADIUS external database

Physical & Environmental

Power Input

100 - 240V internal switching power supply

Power Consumption

11 Watt in Max

Dimensions

441 x 250 x 44 mm (standard rack-mount width, 1 U height)

Operating Temperature

0°C ~ 45°C

Storage Temperature

0°C ~ 60°C



Humidity

5% ~ 95% RH, non-condensing

EMI Certification

- FCC Class A
- CE Class A
- BSMI Class A

Firewall for Workgroups



LISTED
ITE
E141136
66F9

Ordering Information

Workgroup Firewall With VPN & DMZ port DFL-1000 3 10/100Mbps ports

For country-specific power cord, please specify one of the following after the model number:

- /A Includes an American standard power cord
- /BE Includes both EU and U.K. standard power cord
- /N Includes an Australian standard power cord
- /U Includes no power cord
- /E Includes an EU standard power cord
- /B Includes an U.K. standard power cord



Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-949-788-0805	FAX: 1-949-753-7033	www.dlink.com
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095	www.dlink.ca
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	www.dlink.co.uk
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-731-5511	www.dlink.co.uk
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	www.dlink.de
France	TEL: 33-1-30238688	FAX: 33-1-30238689	www.dlink-france.fr
Benelux	TEL: 31-40-2668713	FAX: 31-40-2668666	www.dlink-benelux.nl
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	www.dlink.it
Iberia	TEL: 34-93-4965751	FAX: 34-93-4965701	www.dlinkiberia.es
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	www.dlink.se
Norway	TEL: 47-22-991890	FAX: 47-22-207039	www.dlink.no
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	www.dlink.dk
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661	www.dlink-fi.com
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322	www.dlink-intl.com
Australia	TEL: 61-2-94177100	FAX: 61-2-94171077	www.dlink-me.com
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868	www.dlink.co.jp
China	TEL: 86-10-8809-7777	FAX: 86-10-8809-6789	www.dlink.com.cn
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914	www.dlink-india.com
Middle East	TEL: 202-2456176	FAX: 202-2456192	www.dlink-me.com
South Africa	TEL: 56-2-232-3185	FAX: 56-2-232-0923	www.dlink.cl
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186	www.d-link.co.za
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390	www.dlink.ru
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515	www.dlinktw.com.tw
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299	www.dlink.com.tw



RECYCLABLE
Rev. 01 (Mar. 2002)
Printed in Taiwan