

Features

- Supports control of up to 8 PCs through use of keyboard, mouse and monitor
- Supports hot-plugging: All devices connected to the KVM-140 switch can be added or removed at any time without shutting down the switch.
- Supports hotkey or push button switching
- Auto-scan switches between computers at regular intervals for PC monitoring
- Can be used with DDC, DDC2, and DDC2B KVM cables
- Supports plug and play

Compatibility

- Support for Windows, Linux, Mac OS 9/OS X, and Sun Microsystems Solaris operating systems
- Supports USB mice such as the Microsoft IntelliMouse, IntelliMouse Explorer, Logitech NetMouse, Optical Mouse and more
- Rack mountable in a standard 19" system rack (1U)
- High-quality video resolutions of up to 2048 x 1536

8 Port Rack Mount KVM Switch



The D-Link 8 Port Rack Mount KVM Switch is a local remote management solution which allows you to easily control up to 8 PCs from a single console, allowing you to save time, physical space, and the cost of buying multiple keyboards and monitors.

Versatile Management

Toggle between clients using the front panel buttons or through keyboard hotkeys. A convenient Auto-Scan function allows you to automatically toggle between multiple computers sequentially at preset intervals. The front panel LEDs assist with workstation/server status monitoring. Green LEDs indicate that systems are online, while separate red LEDs indicate when a particular system has been selected for management via console.

Convenient Installation

The sturdy metal chassis is mountable in a standard 19" rack. Target workstations can be connected via keyboard/mouse. A PS/2 keyboard is emulated on each terminal allowing all attached computers to successfully boot without keyboard errors. Hot-pluggable connections allow you to add devices to or remove them from the D-Link KVM-140 8 Port Rack Mount KVM switch without the need to shut it down.



8 Port Rack Mount KVM Switch

Technical Specifications		
Number of Computers Controlled	8	
Selection Method	Push Button and Hotkey (PS/2 Keyboard)	
LEDs	Red for PC Selection Green for PC Online/Ready	
PC Connectors	Video	8 x HDB-15 female
	Keyboard	8 x 6 pin mini-DIN female
	Mouse	8 x 6 pin mini-DIN female
Console Ports	Keyboard	1 x 6 pin mini-DIN 6 female
	Mouse	1 x 6 pin mini-DIN 6 female
	Video	1 x HDB-15 female
DDC, DDC2 monitor	Maximum resolution up to 2048 x 1536 @ 70 Hz	
Hot-swappable	Yes	
Operating Systems Supported	Windows 95/98SE/ME/2000/2003/2008/XP/Vista/7 Netware, Linux, Mac OS 9/OS X, Sun Microsystems	
Certifications	FCC, CE, C-Tick, LVD	
Power	DC 12 V/ 1.25 A power adapter	
Dimensions (L x W x H)	45 x 16 x 4.5 cm (17.7 x 6.3 x 1.77 inches)	
Weight	2.09 kg (4.60 lb)	
Housing Material	Metal	
Operating Temperature	0 to 50°C (32 to 122°F)	
Humidity	0% to 80% Relative Humidity	
Cables Supported	DKVM-CB, DKVM-CB3, DKVM-CB5	

Optional Cables	DKVM-CB	DKVM-CB3	DKVM-CB5
Length	1.8 meters (6 ft)	3 meters (10 ft)	4.5 meters (15 ft)
Weight	165 g (0.36 lb)	334 g (0.74 lb)	443 g (0.98 lb)
VGA	HDB-15 male to male		
PS/2 (Mouse)	6 pin mini-DIN male to male		
PS/2 (Keyboard)	6 pin mini-DIN male to male		



D-Link Corporation
 No. 289 Xinhu 3rd Road, Neihu, Taipei 114, Taiwan
 Specifications are subject to change without notice.
 D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
 All other trademarks belong to their respective owners.
 ©2011 D-Link Corporation. All rights reserved.
 Release 01 (June 2011)