

# **Product Announcement**

### **DP-G301**

Date: Sep 26, 2005

<b>Product Description:</b>	802.11g Wireless Print Server				
Revision:	A1				
Availability:	November, 2005				
Picture:					
Why Sell This Product:	<ul> <li>After the DP-G310 single port 802.11g wireless USB print server, now we're releasing the DP-G301 single port 802.11g wireless parallel print server to complete our wireless print server product line.</li> <li>Replace current DP-311P(802.11b parallel print server) with better performance and is cost-effective.</li> <li>Selling Points</li> <li>High 802.11g WLAN speed, up to 54 Mbps when connected to 802.11g wireless devices.</li> <li>Equipped with Ethernet port, makes it's much easier to set up than DP-311P.</li> <li>This single port wireless 802.11g print server: cost-effective for use in office, school, hospital, government environments.</li> <li>New functions added, including WPA-PSK and UPnP.</li> </ul>				
Key Features:	<ul> <li>Pocket Sized, Light weight</li> <li>Direct Connection to Printer, No Printer Cable Required</li> <li>Parallel Printer Port Supports Bi-Directional Communication</li> <li>Built-in 802.11g Wireless LAN Up to 54Mbps Speed</li> <li>10/100BASE-TX Ethernet Port</li> <li>Operates in Windows, Unix, NetWare, Mac OS Environments</li> <li>Windows-Based Administration Program for Setup/Management of Print Jobs</li> <li>Web-Based Configuration</li> <li>Built-in MIBs for SNMP Management</li> <li>Supports WPA-PSK</li> <li>Supports IPP(Internet Printing Protocol)</li> <li>Supports UPnP(Universal Plug and Play)</li> </ul>				
Technical Details:	-CPU RISC based microprocessor -Flash: 2 M Bytes -SDRAM 8 M Bytes -Printer Port Parallel port *1(1 DB 36-pin male Centronics port, supporting bi-directional communication) -Wireless IEEE 802.11g compliant, supporting up to 54 Mbps -LAN 10/100BASE-TX -Antenna One 2.0dBi dipole antenna -LED indicators Power, LPT, Link/Act - OS supported Microsoft Windows 98/ ME, Windows NT, Windows 2000/ XP/2003 - Mac O.S. 7.6 or above - NetWare 5.x NDPS LPR Remote Printing (TCP/IP) - HP-UX Unix, Sun O.S, Solaris - SCO Unix, AIX, Unix, Linux				
	Transport Protocol:TCP/IP, SMB, NetBEUI, Apple Talk				



D-Link	Pro	oduc	t Annou	ncement		
	TCP/IP Protocols Supported : BOOTP, SNMP, Telnet, TFTP, FTP, LPD, RARP, DHCP, IPP					
	Environmental & Physical Input Power - 5V DC 2.5A - Through external power adapter					
	Dimensions 142 mm (W) x 109 mm (D) x 31 mm (H) (device only)					
	Weight 325 grams					
	Operating Temperature 0 to 50 °C					
	Storage Temperature -25 to 55 °C					
	Humidity 5% to 95% non-condensing					
	Emissions - FCC - CE Class B					
	- C-Tick					
	Box Includes - DP-G301 print server - CD-ROM with Manual and Print Server Administration program - Quick Installation Guide					
EMI/EMC Report	☑FCC No.       ☐ CE No.       ☐ VCCI No.         ☐ CTR-21 No.       ☐ C-Tick No.       ☐ A-Tick No.         ☐ FDA No.       ☐ R&TTE No.       ☐ BSMI No.					
Safety	☑ IC No.         ☐ Others           ☐ TUV No.         ☐ UL No.         ☐ CSA No.					
Packaging Style	☐ CB No ☐ Others ☐ Clamshell ☐ White Box ☑ Gift Box ☐ Bulk ☐ Brown Box ☐ Others					
Packaging Contents:		erver DP-G30				
		A External Poinstallation G	ower Adapter x 1 uide x 1			
	• CD x 1					
UPC Code:		code	Part Number			
	790069	286919	IPG301NEU.A1			
	790069	286926	IPG301ANA.A1			
	790069	286933	IPG301ENA.A1			
	790069	286940	IPG301EEU.A1			
	790069	286957				
	790069	286964				
	790069	286971	NPG301CEU.A1			
	790069	287510	BPG301ANA.A1			



Units Per Carton:	For USA	For EU	For WW	
	10	10	10	
Cartons Per Pallet:	For USA Air:48, Sea: 60	For EU Air:60, Sea: 60	For WW Air:48, Sea: 60	
Dimensions and Weight:	Box:			



## **Product Announcement**

