



## Internet Gateway With Built-in Switch Ports and Print Server

The DI-704P Internet server is an Internet Gateway designed to connect a SOHO or a home to the Internet via a broadband ADSL or cable modem. It allows your entire network to share an ADSL or cable line and a single ISP account to access the Internet simultaneously. With firewall and built-in LAN switch ports, this all-in-one device not only protects your PCs against intruders, it also saves you money while enhancing your LAN workgroup's performance.

### ISP Account Sharing

With a single ISP account, your entire network can logon to the Internet. The device's built-in DHCP server function and Network Address Translator (NAT) automatically create and assign IP addresses for all network users, simplifying users' logon operation while saving you the cost of keeping individual ISP accounts.

### ADSL or Cable Broadband Sharing

Your entire network can access the Internet through a single ADSL or cable connection. Your office needs only one ADSL or cable line, opened to office workers to logon to the Internet 24 hours a day. The DI-704P provides a 10BASE-T port for ADSL/cable modem connection.

### Protection Against Outsiders

The DI-704P provides 2 levels of security support. First, it masks your office workers' IP addresses from others on the Internet, making it more difficult for a hacker to target a computer on your network. Second, it can block and re-direct certain ports to limit the services that outside users can access.

### Virtual Server Mapping

Virtual Server can be used to re-task services to multiple servers. The DI-704P can be set to allow separate FTP, Web, and Multiplayer game servers to share the same Internet-visible IP address while still protecting the servers and local users from hackers.

### VPN Support

The DI-704P provides special support for common VPN implementations including PPTP (Point to Point Tunneling Protocol). It supports multiple PPTP sessions and allows setup of VPN server and VPN clients.

### User-definable Application Sensing Tunnel

The administrator can define the attributes to support special applications requiring multiple connections, such as Internet gaming, video conferencing, and Internet telephony.

### DMZ Host Support

A DMZ setting can be applied to a single client behind the DI-704P to expose it to the Internet and ensure complete Internet application compatibility even if specific ports are not known.

### Cost-saving With 4 Built-in Switched Ports

This device comes with 4 built-in 10/100Mbps switched ports, each providing a LAN bandwidth for office workers and game players. This saves you both the cost of purchasing a separate LAN switch and the trouble of installing it.

### Built-in Print Server Supporting IP Protocol

You can directly attach a parallel printer to the built-in printer port to share this printer out. Fast Ethernet users can print web pages and other files on this printer.

---

### Key Features

- 1 10BASE-T port for cable or ADSL modem connection
- 4 built-in 10/100Mbps switched ports with flow control and NWay auto-negotiation support
- NAT, DHCP support
- Built-in Print Server
- Multiple VPN PPTP sessions, DMZ host support
- Firewall protection against Internet intruders
- Control of LAN users' Internet access rights
- Web-based configuration

## Technical Specifications

## Office LAN

### WAN

**Number of Ports**  
1.0 specifications

**Modem Support**  
- ADSL modem  
- Cable modem

**Internet Support**  
- Network Address Translator Protocol  
- DHCP server

**VPN Support**  
- Multiple PPTP sessions  
- DMZ host

### LAN

**Standards**  
- IEEE 802.3 10BASE-T Ethernet  
- IEEE 802.3u 100BASE-TX Fast Ethernet  
- ANSI/IEEE 802.3 NWay auto-negotiation  
- IEEE 802.3x full-duplex flow control

**LAN Protocol**  
CSMA/CD

**Topology**  
Star

**Number of LAN Ports**  
(Built-in switched ports)  
RJ-45 10BASE-T/100BASE-TX port x 4

**Data Transfer Rates**  
- Ethernet:  
10Mbps (half duplex)  
20Mbps (full duplex)  
- Fast Ethernet:  
100Mbps (half duplex)  
200Mbps (full duplex)

**Network Cables**  
- 10BASE-T:  
1-pair UTP Cat. 3, 4, 5 (100 m)  
EIA/TIA-586 100-ohm STP (100 m)  
- 100BASE-TX:  
UTP Cat. 5 (100m max.)  
EIA/TIA-568 100-ohm STP (100m max.)

**LAN Packet Switching Method**  
Store-and-forward

**MAC Address Filtering Table**  
1K entries per device

**MAC Address Learning**  
Automatic update

**Packet Filtering/Forwarding Rates (half duplex)**  
- Ethernet: 14,880 pps per port  
- Fast Ethernet: 148,810 pps per port

**RAM Buffer**  
32KB x 32 SRAM per device

### Administration & Configuration

**Console Port**  
RS-232 DB-9

**Print Server**  
Supported Protocol IP

**Printer Port**  
1 DB-25 parallel printer Port

## Ordering Information

### Internet Gateway With Built-in Switch Ports and Print Server

**DI-704P** 1 10BASE-T port (for ADSL/cable modem connection)  
4 10/100Mbps LAN switch ports and Parallel printer Server

For external universal switching AC power supply's connector type, please specify one of the following after the model number:

/A For U.S.A., Taiwan and Japan  
/B For U.K.  
/E For Europe  
/N For Australia and China  
/U Includes no AC power supply

# D-Link®



RECYCLABLE

Rev.01 (Dec. 2001)  
Printed in Taiwan

<b>U.S.A</b>	TEL: 1-949-788-0805	FAX: 1-949-753-7033	www.dlink.com
<b>Canada</b>	TEL: 1-905-829-5033	FAX: 1-905-829-5095	www.dlink.ca
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
<b>U.K</b>	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
<b>Germany</b>	TEL: 49-61-96779900	FAX: 49-61-96779900	www.dlink.de
<b>France</b>	TEL: 33-1-30.23.86.88	FAX: 33-1-30.23.86.89	www.dlink.france.fr
<b>Benelux</b>	TEL: 31-40-2668713	FAX: 31-40-2668666	www.dlink-benelux.nl
<b>Italy</b>	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	www.dlink.it
<b>Iberia</b>	TEL: 34-93-4090770	FAX: 34-93-4910795	www.dlinkiberia.es
<b>Sweden</b>	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901	www.dlink.se
<b>Norway</b>	TEL: 47-22-991890	FAX: 47-22-207039	
<b>Denmark</b>	TEL: 45-43-96.90.40	FAX: 45-43-42.43.47	www.dlink.dk
<b>Finland</b>	TEL: 358-9-622-91660	FAX: 358-9-622-91661	www.dlink.fi.com
<b>Singapore</b>	TEL: 65-774-6233	FAX: 65-774-6322	www.dlink-intl.com
<b>Australia</b>	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077	www.dlink.com.au
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9668	www.dlink.co.jp
<b>China</b>	TEL: 86-10-88097777	FAX: 86-10-88096789	
<b>India</b>	TEL: 91-22-652-6696	FAX: 91-22-652-8914	www.dlink-india.com
<b>Middle East</b>	TEL: 20-2-6356176	FAX: 20-2-6356192	www.dlink-me.com
<b>South America</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923	www.dlink.cl
<b>South Africa</b>	TEL: 27(0)126652165	FAX: 27(0)126652186	www.d-link.co.za
<b>Russia</b>	TEL: 7-095-737-3389	FAX: 7-095-737-3390	www.dlink.ru
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515	www.dlinktw.com.tw
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299	www.dlink.com.tw