



## Wireless N300 Router

### 802.11N

High connection rate  
(up to 300Mbps)  
and superior wireless range

### SECURITY

Multiple firewall functions,  
several security standards for  
wireless connection

### OPERABILITY

Easy configuration and  
management through web-  
based interface

### 4-port Switch

The built-in 4-port switch enables you to connect Ethernet-enabled computers, game consoles, and other devices to your network.

### Wireless Interface

Using the DIR-615 device, you are able to quickly create a wireless network at home or in your office, which lets your relatives or employees connect to your wireless network virtually anywhere (within the operational range of your wireless network). The router can operate as an access point for connecting wireless devices of the standards 802.11b, 802.11g, and 802.11n (at the rate up to 300Mbps).

The router supports multiple functions for the wireless interface: several security standards (WEP, WPA/WPA2), MAC address filtering, WPS, WMM.

### Security

The wireless router DIR-615 includes a built-in firewall. The advanced security functions minimize threats of hacker attacks, prevent unwanted intrusions to your network, and block access to unwanted websites for users of your LAN.

### Easy Configuration and Update

You can configure the settings of the multifunction wireless router DIR-615 via the user-friendly web-based interface (the interface is available in several languages).

Now you can simply update the firmware: the router itself finds approved firmware on D-Link update server and notifies when ready to install it.

### Hardware

#### WAN Interface

- 1 10/100BASE-TX Ethernet port for cable or DSL modem or private Ethernet line

#### LAN Interface

- 4 10/100BASE-TX Ethernet ports

#### WLAN Interface

- IEEE 802.11n (up to 300Mbps)
- IEEE 802.11b/g

#### Frequency Range

- 802.11b
  - 2400 ~ 2497MHz ISM band
- 802.11g
  - 2400 ~ 2483.5MHz ISM band
- 802.11n
  - 2400 ~ 2483.5MHz ISM band

#### Data Rate

- 802.11b
  - 11, 5.5, 2, and 1Mbps
- 802.11g
  - 54, 48, 36, 24, 18, 12, 9, and 6Mbps
- 802.11n
  - MCS0 ~ MCS15 (up to 300Mbps)

#### Modulation Schemes

- 802.11b: DQPSK, DBPSK, CCK
- 802.11g: BPSK, QPSK, 16QAM, 64QAM with OFDM
- 802.11n: BPSK, QPSK, 16QAM, 64QAM with OFDM

#### Transmitter Output Power

*The maximum value of the transmitter output power depends upon the radio frequency regulations applied in your country*

- 802.11b (typical at room temperature 25 °C)
  - 16dBm
- 802.11g (typical at room temperature 25 °C)
  - 14dBm (+/-2dBm)
- 802.11n (typical at room temperature 25 °C)
  - 12dBm (+/-2dBm)

#### Receiver Sensitivity

- 802.11b (typical at PER = 8% (1000-byte PDUs))
  - -76dBm at 1, 2, 5.5, 11Mbps
- 802.11g (typical at PER = 10% (1000-byte PDUs))
  - -82dBm at 6Mbps
  - -81dBm at 9Mbps
  - -79dBm at 12Mbps
  - -77dBm at 18Mbps
  - -74dBm at 24Mbps
  - -70dBm at 36Mbps
  - -66dBm at 48Mbps
  - -65dBm at 54Mbps
- 802.11n (typical at PER = 10% (1000-byte PDUs))
  - HT20
    - -82dBm at MCS0/8
    - -79dBm at MCS1/9
    - -77dBm at MCS2/10
    - -74dBm at MCS3/11
    - -70dBm at MCS4/12
    - -66dBm at MCS5/13
    - -65dBm at MCS6/14
    - -64dBm at MCS7/15
  - HT40
    - -82dBm at MCS0/8
    - -79dBm at MCS1/9
    - -77dBm at MCS2/10
    - -74dBm at MCS3/11
    - -70dBm at MCS4/12
    - -66dBm at MCS5/13
    - -65dBm at MCS6/14
    - -64dBm at MCS7/15

# DIR-615

## Specifications

### Software

#### Network Functions

- WAN connection types
  - PPPoE
  - Static IP
  - Dynamic IP
  - PPTP/L2TP + Static IP
  - PPTP/L2TP + Dynamic IP
- DHCP server/client/relay
- VPN pass-through (PPTP/L2TP)
- Dynamic DNS
- Static IP routing
- Remote management
- Network statistics for each interface
- IGMP Proxy
- RIP
- UPnP
- Support of VLAN
- Flow control
- TR-069 client
- WAN ping respond
- Support of SIP
- Support of RTSP

#### Wireless Connection

- Supported security settings
  - WEP
  - WPA/WPA2 Personal
  - WPA/WPA2 Enterprise
- MAC filter
- Managing connected stations
- PIN and PBC methods of WPS
- WMM (Wi-Fi QoS)
- Advanced settings
- Support of client mode

#### Firewall Functions

- Network Address Translation (NAT)
- Stateful Packet Inspection (SPI)
- IP filters
- URL filter
- MAC filter
- DMZ
- Prevention of ARP and DDoS attacks
- Virtual servers

## Wireless N300 Router

### Configuration and Management

- Multilingual web-based interface for configuration and management
- Access via TELNET
- Firmware update via web-based interface
- Automatic notification on new firmware version
- Saving/restoring configuration to/from file
- Support of remote logging
- Automatic synchronization of system time with NTP server and manual time/date setup
- Ping function
- Traceroute utility

### Physical and Environmental

#### LEDs

- Power
- Internet
- WLAN
- 4 LAN LEDs
- WPS

#### Power

- External power adapter DC 5V/1A
- Reset to Factory Defaults button
- WPS button

#### Wall Mounting

- Not possible

#### Operating Temperature

- From 0 to 40 °C (from 32 to 104 °F)

#### Storage Temperature

- From -20 to 65 °C (from -4 to 149 °F)

#### Operating Humidity

- From 10% to 90% non-condensing

#### Storage Humidity

- From 5% to 95% non-condensing

### Ordering Information

#### DIR-615

Wireless N300 Router

The D-Link logo is displayed in a bold, blue, sans-serif font. The letter 'D' is significantly larger than the other letters, and a registered trademark symbol (®) is positioned to the upper right of the 'k'. A horizontal line is drawn below the logo.

Web:

<http://www.dlink.com/corporate/worldwideoffices/>