

SWITCHES



Gigabit xStack Layer 2 Edge Switches - DGS-3400 Series

The xStack DGS-3400 series consists of L2 Gigabit switches that deliver performance, flexibility, security, multi-layer QoS and redundant power supply option for SMB and enterprises.

With high Gigabit port densities for desktop connections, SFP fiber connectivity, 10-Gigabit uplink options and enhanced Layer 2 functions, these switches comprise the workgroup access-layer stack for seamless integration with L3 core switches to form part of a multi-level network structure with high-speed backbone and centralized servers.



DGS-3426/27	Redundancy Power Supply	Physical Stack	10G Expansion
10/100/1000BASE-T x 20 1000BASE-T/SFP Combo Slot x 4 10G Expansion Slot x 2 (DGS-3426) 10G Expansion Slot x 3 (DGS-3427)			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS MLD Snooping Web Authentication 802.1X Authentication MAC Authentication Guest VLAN Quarantine ZoneDefense L4 ACL <p>Optional Accessories: DEM-410X (10G XFP Module), DEM-410CX (10G CX4 Module), DPS-500 (140-Watt RPS), DPS-500DC (140-Watt DC RPS)</p>			
DGS-3426P	Redundancy Power Supply	Physical Stack	10G Expansion
10/100/1000BASE-T x 20 (PoE) 1000BASE-T PoE/SFP Combo Slot x 4 10G Expansion Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS MLD Snooping Web Authentication 802.1X Authentication MAC Authentication Guest VLAN Quarantine ZoneDefense L4 ACL <p>Optional Accessories: DEM-410X (10G XFP Module), DEM-410CX (10G CX4 Module), DPS-600 (500-Watt RPS)</p>			
DGS-3450	Redundancy Power Supply	Physical Stack	10G Expansion
10/100/1000BASE-T x 44 1000BASE-T/SFP Combo Slot x 4 10G Expansion Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS MLD Snooping Web Authentication 802.1X Authentication MAC Authentication Guest VLAN Quarantine ZoneDefense L4 ACL <p>Optional Accessories: DEM-410X (10G XFP Module), DEM-410CX (10G CX4 Module), DPS-500 (140-Watt RPS), DPS-500DC (140-Watt DC RPS)</p>			
DGS-3426G	Redundancy Power Supply	Physical Stack	10G Expansion
SFP 1000BASE-T x 20 1000BASE-T/SFP Combo Slot x 4 10G Expansion Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS MLD Snooping Web Authentication 802.1X Authentication MAC Authentication Guest VLAN Quarantine ZoneDefense L4 ACL <p>Optional Accessories: DEM-410X (10G XFP Module), DEM-410CX (10G CX4 Module), DPS-500 (140-Watt RPS), DPS-500DC (140-Watt DC RPS)</p>			



Fast Ethernet xStack Layer 2 Edge Switches - DES-3528/52 Series

The xStack DES-3528/52 series consists of L2 10/100Mbps switches that deliver performance, flexible expansion, robust security, multi-layer QoS and redundant power supply option.

DES-3528/52 series simplifies and speeds up management tasks through a web browser from any workstation with a single unique IP address to monitor, maintain, and configure multiple switches. The stack is managed as a single object with all units identified by a single IP address.

DES-3528/52 series provides complete security features for connectivity and access control with central management for administration access via RADIUS and TACACS+.

DES-3528/52	Redundancy Power Supply	Physical Stack	
10/100BASE-TX x 24/48 1000BASE-T/SFP Combo Slot x 2 1000BASE-T/Stacking Port x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) MLD Snooping Web Authentication MAC Authentication Traffic Segmentation D-Link Safeguard Engine 802.1X Authentication <p>Optional Accessories: DPS-200 (60-Watt RPS)</p>			
DES-3528DC	Redundancy Power Supply	Physical Stack	DC Power Supply
10/100BASE-TX x 24 1000BASE-T/SFP Combo Slot x 2 1000BASE-T/Stacking Port x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) MLD Snooping Web Authentication MAC Authentication Traffic Segmentation D-Link Safeguard Engine 802.1X Authentication 			
DES-3528P	Redundancy Power Supply	Physical Stack	PoE Supply
10/100BASE-TX x 24 1000BASE-T/SFP Combo Slot x 2 1000BASE-T/Stacking Port x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) MLD Snooping Web Authentication MAC Authentication Traffic Segmentation D-Link Safeguard Engine 802.1X Authentication <p>Optional Accessories: DPS-600 (500-Watt RPS)</p>			



Fast Ethernet Layer 2 Switches DES-3200 Series

DES-3200 Series is the new member of D-Link Layer 2 Managed Switch product line. DES-3200 Series provides 8/16/24 10/100Mbps Fast Ethernet ports with 2/2/4 combo 1000Bast-T/SFP ports. 10/100/1000Mbps Gigabit Ethernet ports allow you to connect uplink switches. The SFP ports provide the fiber connectivity to FTTH environment.

DES-3200-10	Internal Power Supply	11" Rackmount / Desktop	
10/100BASE-TX x 8 1000BASE-T/SFP Combo Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS IP MAC Port Binding Port Security Q-in Q ACL 			
DES-3200-18	Internal Power Supply	11" Rackmount / Desktop	
10/100BASE-TX x 16 1000BASE-T/SFP Combo Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS IP MAC Port Binding Port Security Q-in Q ACL 			
DES-3200-28	Internal Power Supply	19" Rackmount	
10/100BASE-TX x 24 1000BASE-T/SFP Combo Slot x 4			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS IP MAC Port Binding Port Security Q-in Q ACL 			
DES-3200-28F	Internal Power Supply	19" Rackmount	
SFP 100BASE-FX x 24 1000BASE-T/SFP Combo Slot x 4			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS IP MAC Port Binding Port Security Q-in Q ACL 			

ETTH Solution includes: DIR-100/F, DES-1008F, DES-1008FL/PRO, DES-1008FR/PRO



Gigabit Secure Switches - DGS-3200 Series

DGS-3200 series consists of Security Gigabit switches that deliver high performance, flexible expansion and robust security. It executes firm network security and provides ACL functionalities to secure the internal IT network against external virus from invading the LAN.

DGS-3200 series offers extensive endpoint security features to protect the network. Apart from executing firm network security, it also provides user identity control by implementing host-based 802.1X authentication/authorization, along with clientless Web-based access control (WAC) and MAC-based access control (MAC) for easy deployment.

DGS-3200-10	Internal Power Supply	Fanless	
10/100/1000BASE-T x 8 1000BASE-T/SFP Combo Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS MLD Snooping Web-Based Access Control 802.1X Authentication MAC-Based Access Control Guest VLAN Microsoft NAP ZoneDefense L4 ACL 			
DGS-3200-16	Internal Power Supply	Smart Fan	
10/100/1000BASE-T x 14 1000BASE-T/SFP Combo Slot x 2			
<ul style="list-style-type: none"> Virtual Stack (SIM) SNMP 4K VLAN QoS MLD Snooping Web-Based Access Control 802.1X Authentication MAC-Based Access Control Guest VLAN Microsoft NAP ZoneDefense L4 ACL 			