



DEM-312GT2 **1000Base-SX+ Multi-Mode SFP transceiver (up to 2 km)**

The DEM-312GT2 Gigabit SFP fiber transceiver is external transceiver designed for insertion in SFP (Small Form-Factor Pluggable) slot of network device for transmission and reception of data signals on the fiber cables. This transceiver provides high-speed and reliable distance (up to 2 km) data transfer.

The DEM-312GT2 transceiver uses standard duplex LC connector for fiber cable connection. It conforms to industry standards and is interoperable with D-Link Gigabit switches. All D-Link transceivers are hot-pluggable. Hot-swap capability allows network administrators to plug or unplug it from the SFP slot without having to turn off the power of the connected device.

1000Base-SX+ Multi-Mode SFP transceiver (up to 2 km)

General features	
Standard	· IEEE 802.3z 1000Base-SX+
Wavelength	· 1310 nm
Data Rate	· 1.25 Gbps
Connector	· Duplex LC
Maximum Fiber Cable Length	· 2 km
Transmit Power Range	· -8 to -15 dBm
Receive Power Range	· -3 to -20 dBm
Sensitivity	· -20 dBm
Supported Features	· Hot swap · MSA compliant · RoHS compliant
Physical Parameters	
Power Support	· 3.3 V
Supply Current	· 220 mA
Temperature	· Operating: 0° to 70°C · Storage: -40° to 85°C
Humidity	· Operating: 0% to 85% · Storage: 0% to 85%
Dimensions	· 55.4 mm x 13.7 mm x 8.5 mm
Order info	
DEM-312GT2	1000Base-SX+ Multi-Mode SFP transceiver (up to 2 km)

Updated 09/07/2021