



DEM-315GT

1000Base-ZX Single-Mode SFP transceiver (up to 80 km)

The DEM-315GT Gigabit SFP fiber transceiver is external transceiver designed for insertion in SFP (Small Form-Factor Pluggable) slot of network device for transmission and reception of data signals on the fiber cables. This transceiver provides high-speed and reliable long-distance (up to 80 km) data transfer.

The DEM-315GT transceiver uses standard duplex LC connector for fiber cable connection. It conforms to industry standards and is interoperable with D-Link Gigabit switches. All D-Link transceivers are hot-pluggable. Hot-swap capability allows network administrators to plug or unplug it from the SFP slot without having to turn off the power of the connected device.

1000Base-ZX Single-Mode SFP transceiver (up to 80 km)

General features	
Standard	· IEEE 802.3z 1000Base-ZX
Wavelength	· 1550 nm
Data Rate	· 1.25 Gbps
Connector	· Duplex LC
Fiber Type	· 9/125 um Single-mode Fiber
Maximum Fiber Cable Length	· 80 km
Transmit Power Range	· 5 to 0 dBm
Receive Power Range	· -3 to -24 dBm
Sensitivity	· -24 dBm
Supported Features	· Hot swap · MSA compliant · RoHS compliant
Physical Parameters	
Power Support	· 3.3 V
Supply Current	· 300 mA
Temperature	· Operating: 0° to 70°C · Storage: -40° to 85°C
Humidity	· Operating: 0% to 85% · Storage: 0% to 85%
Dimensions	· 55.4 mm x 13.7 mm x 8.5 mm
Certificates	· Class 1 laser: EN 60825-1 · FDA 21 CFR 1040.10 и 1040.11
Order info	
DEM-315GT	1000Base-ZX Single-Mode SFP transceiver (up to 80 km)

Updated 13/07/2021