



## DEM-Q2810Q-LR4

### 100GBase-LR4 Single-Mode QSFP28 transceiver (up to 10 km)

D-Link's 100G QSFP28 Module series are hot-swappable QSFP28 transceivers that plug into QSFP28 slots on switches and support 100G Ethernet. The D-Link 100GBase QSFP28 Module Series transceivers offer customers a wide variety of 100G Ethernet connectivity options for data centers, enterprise wiring closets, and service provider transport applications.

#### Quad Small Form-factor Pluggable 28 Format

The transceivers use the Quad Small Form-factor Pluggable 28 format (QSFP28) connectors, which integrate four independent transmitting and receiving channels. QSFP28 supports up to 25 Gb/s per channel for applications such as 100G Ethernet.

#### Hot-Pluggable

All D-Link transceivers are hot-pluggable. Hot-swap capability allows network administrators to plug or unplug it from the SFP slot without having to turn off the power of the connected device.

#### 100G Ethernet speeds

The transceivers support 100G Ethernet, which results in very fast data transmissions of up to 100 Gbit/s, that enables the switches to handle fast and heavy data transmissions, making it suitable for business needs.

**100GBase-LR4 Single-Mode QSFP28 transceiver (up to 10 km)**

<b>General features</b>	
<b>Standard</b>	· IEEE 802.3ba 100GBase-LR4
<b>Wavelength</b>	· 1295.56 nm · 1300.05 nm · 1304.58 nm · 1309.14 nm
<b>Data Rate</b>	· 100 Gbps
<b>Connector</b>	· Duplex LC
<b>Maximum Fiber Cable Length</b>	· 10 km
<b>Transmit Power Range</b>	· 4.5 to -4.3 dBm
<b>Receive Power Range</b>	· 4.5 to -10.6 dBm
<b>Sensitivity</b>	· -8.6 dBm
<b>Supported Features</b>	· Hot swap · MSA compliant · RoHS compliant
<b>Physical Parameters</b>	
<b>Power Support</b>	· 3.3 V
<b>Supply Current</b>	· 1.06 A
<b>Power Consumption</b>	· 3.5 W
<b>Temperature</b>	· Operating: 0° to 70°C · Storage: -40° to 85°C
<b>Humidity</b>	· Operating: 0% to 85% · Storage: 0% to 85%
<b>Dimensions</b>	· 70 mm x 18.3 mm x 8.5 mm
<b>Order info</b>	
<b>DEM-Q2810Q-LR4</b>	100GBase-LR4 Single-Mode QSFP28 transceiver (up to 10 km)

Updated 19/08/2021