



## 8-PORT 10/100 SWITCH

### SILENT OPERATION


Fanless design provides noise-free operation

### PLUG AND PLAY

Auto MDI/MDIX simplifies cable connections

### COMPACT DESIGN

Stylish, compact design can be placed anywhere



### AUTO-SENSING 10/100 PORTS

The DES-1008A uses auto-sensing 10/100 Mbps ports, allowing a small workgroup to flexibly connect to Ethernet and Fast Ethernet devices to create an integrated network. These ports detect the network speed and auto-negotiate between 10BASE-T and 100BASE-TX, as well as between full and half-duplex, allowing you to get the maximum speed possible for each device connected to your network.

### AUTO MDI/MDIX CROSSOVER

All ports support automatic MDI/MDIX crossover, eliminating the need for crossover cables or uplink ports. Each port can be plugged directly to a server, hub, router, or switch using regular straight-through twisted-pair Ethernet cables.



### FLOW CONTROL FOR SECURE TRANSMISSION

802.3x flow control on each port minimizes dropped packets when the port's receiving buffer is full. This gives you a more reliable connection for all of your connected devices.

## WHAT THIS PRODUCT DOES

The DES-1008A 8-Port 10/100 Mbps Switch is an 8-port 10/100 Mbps Fast Ethernet switch that allows you to quickly set up a wired network. Connect the DES-1008A to multiple computers together to share files and folders, or connect it to a router to share an Internet connection.

## YOUR NETWORK SETUP



8 RJ-45 10/100 BASE-TX PORTS  
Connects to computers, print servers, or network storage

## TECHNICAL SPECIFICATIONS

### KEY FEATURES

- Inexpensive Fast Ethernet solution for Home/SOHO
- 8 10/100 Mbps Fast Ethernet ports
- Auto MDI/MDIX crossover for all ports
- Store-and-forward switching scheme
- Full/half-duplex for Ethernet/Fast Ethernet speeds
- IEEE 802.3x Flow Control
- Plug-and-play installation
- RoHS compliant

### SWITCHING FABRIC

- 1.6 Gbps switching fabric

### STANDARDS

- IEEE 802.3 10BASE-T Ethernet (twisted-pair copper)
- IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper)
- ANSI/IEEE 802.3 NWay auto-negotiation
- IEEE 802.3x flow control

### PROTOCOL

- CSMA/CD

### DATA TRANSFER RATES

- Ethernet:
  - 10 Mbps (half duplex)
  - 20 Mbps (full duplex)
- Fast Ethernet:
  - 100 Mbps (half duplex)
  - 200 Mbps (full duplex)

### TOPOLOGY

- Star

### MEDIA INTERFACE EXCHANGE

- Auto MDI/MDIX adjustment for all ports

### NETWORK CABLES

- 10BASE-T:
  - UTP CAT 3/4/5/5e (100 m max.)
  - EIA/TIA-568 100-ohm STP (100 m max.)
- 100BASE-TX
  - UTP CAT 5/5e (100 m max.)
  - EIA/TIA-568 100-ohm STP (100 m max.)

### LED INDICATORS

- Per port:
  - Link/Activity
- Per device:
  - Power

### TRANSMISSION METHOD

- Store-and-forward

### MAC ADDRESS TABLE

- 1K entries per device

### MAC ADDRESS LEARNING

- Automatic update

### PACKET FILTERING/FORWARDING RATES

- Ethernet: 14,880 pps per port
- Fast Ethernet: 148,800 pps per port

### RAM BUFFER

- 57 KBytes per device

### DC INPUT

- External 5V/1A power adapter

### POWER CONSUMPTION

- Power On (Standby):
  - DC input: 0.3 watts
  - AC input: 0.5 watts
- Maximum:
  - DC input: 1.6 watts
  - AC input: 2.5 watts

### HEAT DISSIPATION

- Power On (Standby):
  - AC input: 1.706 BTU/h
- Maximum:
  - AC input: 8.53 BTU/h

### OPERATING TEMPERATURE

- 0 to 40 °C (32 to 104 °F)

### STORAGE TEMPERATURE

- -10 to 70 °C (14 to 158 °F)

### OPERATING HUMIDITY

- 10% to 90% RH non-condensing

### STORAGE HUMIDITY

- 5% to 90% RH non-condensing

### DEVICE DIMENSIONS (W x D x H)

- 128 x 68.5 x 25.4 mm (5.0 x 2.7 x 1.0 inches)

### CERTIFICATIONS

- FCC Class B
- ICES-003 Class B
- CE Class B
- C-Tick Class B
- cUL
- LVD



D-Link Corporation  
No. 289 Xinhu 3rd Road, Neihu, Taipei 114, Taiwan  
Specifications are subject to change without notice.  
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.  
All other trademarks belong to their respective owners.  
©2010 D-Link Corporation. All rights reserved.  
Release 02 (May 2010)