

*Unleash the Power  
of Hi-Speed USB*

DFB-A5



- Two Hi-Speed 480Mbps<sup>1</sup> USB 2.0 Ports
- Three 400Mbps Firewire Ports
- Backwards Compatible with USB 1.1 and 1.0
- Plug-&-Play

## USB 2.0 & Firewire Combo PCI Adapter

**Integrated USB 2.0 and Firewire**  
The DFB-A5 is a 2-port Hi-Speed USB 2.0 and 3-port 1394 Firewire combo PCI adapter for desktop computers. The DFB-A5 is designed to work with DV camcorders, mice, keyboards, external CD-R/RW's, external hard drives, PC cameras, and any other USB or Firewire enabled device. It is 40 times faster than previous USB adapters with Hi-Speed USB 2.0 support and supports up to 400Mbps with integrated Firewire in one convenient upgrade package for desktop computers.

**2-Port Hi-Speed USB 2.0**  
Each of the two USB 2.0 ports transfers data at 480Mbps<sup>1</sup> (Megabits per second), making it ideal for external storage, backup, networking and digital video. The DFB-A5 is certified to USB 2.0 standards and is backward compatible with USB 1.0 and USB 1.1.

**3-Port Firewire (1394)**  
The DFB-A5's three Firewire ports support transfer rates up to 400Mbps, making it ideal for home video editing using Digital Video (DV) ready camcorders and external storage solutions. With the bundled video editing software, the DFB-A5 offers a complete DV editing package perfect for any home video enthusiast.

1: Maximum transfer rate based on USB 2.0 specification. Actual data throughput will vary.



# USB 2.0 & Firewire Combo PCI Adapter



DFB-A5

## SPECIFICATIONS

### Standards

- USB Specification Version 2.0
- USB Specification Version 1.1
- USB Specification Version 1.0
- OHCI 1.1 (Open Host Controller Interface)
- EHCI .95 (Enhanced Host Controller Interface)
- IEEE 1394-1395 Compliant
- 1394A Compatible

### Compatible Operating Systems

- Microsoft Windows XP, ME, 2000, 98SE with USB Support
- Mac OS X 10 and above with USB Support

### Ports

- Two downstream USB Type "A" receptacles
- Three 6-Pin 1394 Firewire receptacles

### Connectivity

Up to 127 devices by cascading multiple hubs

### Supplied Current

500mA per port

### Humidity

5% to 95%, non-condensing

### Certifications

USB-IF

### Compliances

CE, FCC Class B, VCCI, UL

### Card Type

PCI Version 2.2

### Warranty

1 Year

### Operating Temperature

0°C to 40°C

### Storage Temperature

0 to 95%, non-condensing

Technology

Hi-Speed USB 2.0 - 480Mbps

1394 Firewire - 400Mbps

USB 1.1 - 12Mbps


1X

Up to 40X

Performance<sup>1</sup>

The DFB-A5 performs up to 40 times faster than USB 1.1 by utilizing the 480Mbps<sup>1</sup> throughput speed of Hi-Speed USB 2.0.

## Typical DFB-A5 Installation



D-Link Systems, Inc. 17595 Mt. Herrmann Fountain Valley CA 92708-4160 www.dlink.com  
©Copyright D-Link Systems, Inc. 2004. All rights reserved. D-Link® is a registered trademark of D-Link Systems, Inc.  
Other trademarks or registered trademarks are the property of their respective manufacturers or owners.  
Price and specifications are subject to changes without notice. See inside package for warranty details.

<sup>1</sup>24/7 Tech Support is available only in USA.

<sup>2</sup>Maximum transfer rate based on USB 2.0 specifications.  
Actual data throughput will vary.

**D-Link**<sup>®</sup>  
Building Networks for People