

# REALTEK

---

## Quick Guide for wpa\_supplicant Wi-Fi P2P test

Date: 2020/12/18

Version: 1.2

### (1) Release note

Document Version	Note
V1.0	1. First release
V1.1	1. Add case “Connect in PBC and establish a persistent P2P group”

	2. Add case “Re-invoke a persistent P2P group”
V1.2	1. New (7) Improve the success rate of P2P nego to GO

Realtek


## (2) P2P description:

Wi-Fi Direct ( P2P ) is a technology developed by Wi-Fi Alliance. It is a solution for Wi-Fi device-to-device connectivity. And it is also backward compatible with existing Wi-Fi Certified devices.

In usual, there are 3 stages in the Wi-Fi Direct scenario.

1. “Device Discovery”
2. “Group Formation” + “Provisioning” (WPS)
3. “Device connection” (DHCP)

The following picture will provide the overall concept for Wi-Fi Direct functionality and it will also contain these 3 stages described above.



**Figure1: Wi-Fi Direct Overview**

The figure1 describes the basic Wi-Fi Direct scenario and this document will use this figure to do connection test.

## 1. Enable P2P

In this case, there are two Wi-Fi devices which both support the Wi-Fi Direct functionality. We can use start wpa\_supplicant to enable the Wi-Fi Direct function of Realtek Wi-Fi driver (enable P2P).

If use driver version 5.8 or later and it supports “rtw\_sel\_p2p\_iface” when insmod, you need to use this parameter to select p2p interface when driver define “CONFIG\_CONCURRENT\_MODE”.

**Ex:** #> insmod 8821cu.ko rtw\_sel\_p2p\_iface=0

(This example select interface 0 to be p2p interface, otherwise default use interface 1 to be p2p interface)

If use driver version 5.11 or later, it supports modify “rtw\_sel\_p2p\_iface” by Makefile. You need to add the “CONFIG\_SEL\_P2P\_IFACE” to your platform dependent configuration section to select p2p interface when driver define “CONFIG\_CONCURRENT\_MODE”.

**Ex:**

```
ifeq ($(CONFIG_PLATFORM_RTK119X_AM), y)
EXTRA_CFLAGS += -DCONFIG_PLATFORM_RTK119X_AM
EXTRA_CFLAGS += -DCONFIG_LITTLE_ENDIAN
EXTRA_CFLAGS += -DCONFIG_TRAFFIC_PROTECT
EXTRA_CFLAGS += -DCONFIG_CONCURRENT_MODE -DCONFIG_FULL_CH_IN_P2P_HANDSHAKE
EXTRA_CFLAGS += -DCONFIG_SEL_P2P_IFACE=2
EXTRA_CFLAGS += -DCONFIG_IFACE_NUMBER=3
EXTRA_CFLAGS += -DCONFIG_IOCTL_CFG80211 -DRTW_USE_CFG80211_STA_EVENT

ifeq ($(CONFIG_USB_HCI), y)
EXTRA_CFLAGS += -DCONFIG_USE_USB_BUFFER_ALLOC_TX
endif
```

(This example select interface 2 to be p2p interface, otherwise default use interface 1 to be p2p interface)

Note: The method from the previous paragraph has higher priority than this method.

## 2. Scanning P2P Device

After enabling the P2P functionality of the Wi-Fi driver, the P2P device1 got to find out how many other P2P devices exist in the environment. We can do the this via wpa\_supplicant command.

**Ex:** #> wpa\_cli p2p\_find

**Ex:** #> wpa\_cli p2p\_listen

## 3. Start Group Negotiation + Provisioning

In the Wi-Fi Direct scenario, one of the P2P devices will become a group owner (almost the same as the SoftAP) and the other P2P device will become an 802.11 client to connect to that group owner. The stage3 “Start Group Negotiation” is the procedure to determine which P2P device should be the group owner/client.

After confirming the role for both P2P Device1 and P2P Device2, the P2P device the wpa\_supplicant in the background and use the PIN CODE or PBC to perform the WPS procedure.

“go\_intent” is a value from 0 ~ 15. This value will provide the degree information to want to be the group owner. “intent=15” means this Wi-Fi driver must be the group owner. The default intent value is 1.

“pbc” is wps config method. It can be “pbc” or “pin”

**Ex:** #> wpa\_cli -i wlan0 p2p\_connect 00:e0:4c:02:80:6e pbc go\_intent=7

## 4. DHCP

The Wi-Fi Direct Specification required that the P2P device which becomes the group owner should also provide the DHCP server application in their system. The DHCP server should be launched and be ready to provide the IP address to the DHCP client. The specification also required that the P2P device which becomes the P2P client should launch the DHCP client application to acquire the IP address from the P2P group owner after the wpa\_supplicant established the 802.11 connection with AP successfully.

### (3) Support version:

- cfg80211 only

### (4) How to start wpa\_supplicant:

- Please reference another document under document folder. (wpa\_cli\_with\_wpa\_supplicant.pdf)

### (5) P2P commands

Note: Can reference “README-P2P” file under wpa\_supplicant folder

#### Device Discovery

Command	Description
p2p_find [timeout in seconds]	Enables discovery – start sending probe request frames

<b>p2p_stop_find</b>	Stops discovery, or whatever you are doing (listen mode, connection process etc.)
<b>p2p_listen</b> [timeout in seconds]	Enable listen mode

## Device Discovery : Discovered Peers List

Command	Description
<b>p2p_peers</b> [discovered]	Shows list of discovered peers (with 'discovered' – shows only fully discovered peers)
<b>p2p_peer</b> <P2P Device Address>	Show detailed information about discovered peers
<b>p2p_flush</b>	Flush p2p_state, and clears the discovered peer list

## Group Formation

Command	Description
<b>p2p_connect</b> <peer device address> <pbcc/pin> [GO_intent=<0-15>] [auth/join]	GO_intent – initiate connection to another device (using entered group intent) Auth – WPS authorize incoming connection Join – connect to an existing GO No input – initiate connection using default GO intent
<b>p2p_group_add</b> [freq=<freq in MHz>]	Become an autonomous GO freq=<freq in MHz> can be used to force the GO to be started on a specific frequency.
<b>p2p_group_remove</b>	Remove device from group, return to device mode if acting as GO or autonomous GO

## Group Formation : GO WPS authorizations

Command	Description
<b>wps_pbcc</b>	Start WPS PBC method
<b>wps_pin</b> <any/address> <PIN>	Start WPS PIN method

## Others

Command	Description
<b>p2p_prov_disc</b> <peer device address> <display/keypad/pbc> [join/auto]	Send P2P provision discovery request to the specified peer.
<b>p2p_invite</b>	Invite a peer to join a group or to reinvite a persistent group.

## (6) P2P Use case

### Case 1 : Connect in PBC (Push button Control)

#### Case 1-1 : DUT #1 & DUT #2 use p2p\_find to find out each other

Step #	DUT #1	DUT #2	Comments
1	p2p_find 30	p2p_find 30	Find p2p device
2	p2p_peers	p2p_peers	verify p2p candidates MAC ADDRESS
3	p2p_connect <DUT#2_MAC_ADDRESS> pbc go_intent=7		go_intent=7 means that there a same chance for both DUTs to become GO go_intent= 15 means that DUT will become GO go_intent= 0 means that DUT will become Client
4		p2p_connect <DUT#1_MAC_ADDRESS> pbc	

## DUT\_1\_case\_1-1

**[root]# ./wpa\_cli -i wlan0 status**

wpa\_state=DISCONNECTED

p2p\_device\_address=00:e0:4c:02:80:45

address=00:e0:4c:02:80:45

**[root]# ./wpa\_cli -i wlan0 p2p\_find 30**

OK

**[root]# ./wpa\_cli -i wlan0 p2p\_peers**

00:e0:4c:02:80:6e

**[root]# ./wpa\_cli -i wlan0 p2p\_connect 00:e0:4c:02:80:6e pbc go\_intent=7**

OK

**[root]# ./wpa\_cli -i wlan0 status**

bssid=00:e0:4c:02:80:6e

ssid=DIRECT-Cc

id=2

mode=station

pairwise\_cipher=CCMP

group\_cipher=CCMP

key\_mgmt=WPA2-PSK

wpa\_state=COMPLETED

ip\_address=192.168.42.33

p2p\_device\_address=00:e0:4c:02:80:45

address=00:e0:4c:02:80:45

## DUT\_2\_case\_1-1

**[root]# ./wpa\_cli -i wlan0 status**

wpa\_state=DISCONNECTED

p2p\_device\_address=00:e0:4c:02:80:6e

address=00:e0:4c:02:80:6e

**[root]# ./wpa\_cli -i wlan0 p2p\_find 30**

OK

**[root]# ./wpa\_cli -i wlan0 p2p\_peers**

00:e0:4c:02:80:45

**[root]# ./wpa\_cli -i wlan0 p2p\_connect 00:e0:4c:02:80:45 pbc**

OK

**[root]# ./wpa\_cli status**

bssid=00:e0:4c:02:80:6e

ssid=DIRECT-Cc

id=1

mode=P2P GO

pairwise\_cipher=CCMP

group\_cipher=CCMP

key\_mgmt=WPA2-PSK

wpa\_state=COMPLETED

ip\_address=192.168.42.1

p2p\_device\_address=00:e0:4c:02:80:6e

address=00:e0:4c:02:80:6e



### Case 1-2 : DUT #2 listen only DUT #1 use p2p\_find to find out DUT #2

Step #	DUT #1	DUT #2	Comments
1	p2p_find 30	p2p_listen 60	Find p2p device
2	p2p_peers		verify p2p candidates MAC ADDRESS
3	p2p_connect <DUT#2_MAC_ADDRESS> pbc		go_intent=7 means that there a same chance for both DUTs to become GO go_intent= 15 means that DUT will become GO go_intent= 0 means that DUT will become Client
4		p2p_connect <DUT#1_MAC_ADDRESS> pbc	

## DUT\_1\_case\_1-2

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:6e

```
[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:6e pbc
```

OK

```
[root]# ./wpa_cli -i wlan0 status
```

bssid=00:e0:4c:02:80:6e

ssid=DIRECT-5e

id=2

mode=station

pairwise\_cipher=CCMP

group\_cipher=CCMP

key\_mgmt=WPA2-PSK

wpa\_state=COMPLETED

ip\_address=192.168.42.33

p2p\_device\_address=00:e0:4c:02:80:45

address=00:e0:4c:02:80:45

## DUT\_2\_case\_1-2

```
[root]# ./wpa_cli -i wlan0 p2p_listen 60
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:45 pbc
```

OK

```
[root]# ./wpa_cli -i wlan0 status
```

bssid=00:e0:4c:02:80:6e

ssid=DIRECT-5e

id=1

mode=P2P GO

pairwise\_cipher=CCMP

group\_cipher=CCMP

key\_mgmt=WPA2-PSK

wpa\_state=COMPLETED

ip\_address=192.168.42.1


p2p\_device\_address=00:e0:4c:02:80:6e

address=00:e0:4c:02:80:6e

### Case 1-3 : DUT #2 is Android device and use UI to connect P2P

Step #	DUT #1	DUT #2 (Android device)	Comments
		Enter Wi-Fi Direct or P2P page	
1	p2p_find 30	Push "SEARCH FOR DEVICES"	Find p2p device
2	p2p_peers		verify p2p candidates MAC ADDRESS
3	p2p_connect <DUT#2_MAC_ADDRESS> pbc		
4		Push "ACCEPT"	
			<b>Note: When DUT#1 is GO. It maybe need to start a DHCP server to assign a IP to Android device. (Some Android device no IP will trigger disconnect)</b>

DUT 1 case 1-3



mode=P2P GO  
pairwise\_cipher=CCMP  
group\_cipher=CCMP  
key\_mgmt=WPA2-PSK  
wpa\_state=COMPLETED  
p2p\_device\_address=00:e0:4c:05:50:c1  
address=00:e0:4c:05:50:c1

DUT\_2\_case\_1-3

- 1.
- 2.
- 3.
- 4.

## Case 2 : Connect in PBC (Push button Control)

where DUT #1 is defined as the Auto Group Owner

Step #	DUT #1	DUT #2	Comments
1	p2p_find 30	p2p_find 30	
2	p2p_peers	p2p_peers	verify p2p candidates MAC ADDRESS
3	p2p_group_add		Define DUT #1 as GO
4	wps_pbc		
5		p2p_connect <DUT#1_MAC_ADDRESS> pbc join	

### DUT\_1\_case\_2

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:6e

```
[root]# ./wpa_cli -i wlan0 p2p_group_add
```

OK

```
[root]# ./wpa_cli -i wlan0 wps_pbc
```

OK

### DUT\_2\_case\_2

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:45

```
[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:45 pbc join
```

OK

## Case 3 : Connect in PIN (PIN Number) where DUT

### #1 is defined as the Auto Group Owner

Step #	DUT #1	DUT #2	Comments
1	p2p_find 30	p2p_find 30	
2	p2p_peers	p2p_peers	verify p2p candidates MAC ADDRESS
3	p2p_group_add		Define DUT #1 as GO
4	wps_pin any		verify the <DUT#1_PIN_CODE>, will appear on the terminal
5		p2p_connect <DUT#1_MAC_ADDRESS> <DUT#1_PIN_CODE> join	

#### DUT\_1\_case\_3

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:6e

```
[root]# ./wpa_cli -i wlan0 p2p_group_add
```

OK

```
[root]# ./wpa_cli -i wlan0 wps_pin any
```

3760533

#### DUT\_2\_case\_3

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:45

```
[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:45 3760533 join
```

OK

## Case 4 : Connection using PIN code

Step #	DUT #1	DUT #2	Comments
1	p2p_find 30	p2p_find 30	
2	p2p_peers	p2p_peers	verify p2p candidates MAC ADDRESS
3	p2p_connect <DUT#2_MAC_ADDRESS> pin auth		verify the <DUT#1_PIN_CODE>, will appear on the terminal
4		p2p_connect <DUT#1_MAC_ADDRESS> <DUT#1_PIN_CODE>	

DUT_1_case_4	DUT_2_case_4
<pre>[root]# ./wpa_cli -i wlan0 p2p_find 30</pre> <p>OK</p> <pre>[root]# ./wpa_cli -i wlan0 p2p_peers</pre> <p>00:e0:4c:02:80:6e</p> <pre>[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:6e pin auth</pre> <p>53617170</p>	<pre>[root]# ./wpa_cli -i wlan0 p2p_find 30</pre> <p>OK</p> <pre>[root]# ./wpa_cli -i wlan0 p2p_peers</pre> <p>00:e0:4c:02:80:45</p> <pre>[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:45 53617170</pre> <p>OK</p>

## Case 5: Connect in PBC (Push button Control) and establish a persistent P2P group

Step #	DUT #1	DUT #2	Comments
1	p2p_find 30	p2p_find 30	
2	p2p_peers	p2p_peers	verify p2p candidates MAC ADDRESS
3	p2p_connect <DUT#2_MAC_ADDRESS> pbc persistent go_intent=7		go_intent=7 means that there a same chance for both DUTs to become GO go_intent= 15 means that DUT will become GO go_intent= 0 means that DUT will become Client
4		p2p_connect <DUT#1_MAC_ADDRESS> pbc persistent	

### DUT\_1\_case\_5

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:6e

```
[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:6e pbc persistent
```

go\_intent=7

OK

### DUT\_2\_case\_5

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:45

```
[root]# ./wpa_cli -i wlan0 p2p_connect 00:e0:4c:02:80:45 pbc persistent
```

OK



## Case 6: Re-invoke a persistent P2P group where DUT#1 was the Group Owner of the persistent P2P group

Step #	DUT #1	DUT #2	Comments
	p2p_find 30	p2p_find	Make <b>DUT #2</b> keep in find phase with no time limit
	p2p_peers	p2p_peers	verify p2p candidates MAC ADDRESS
	list_networks	list_networks	verify the persistent P2P group Network ID
	p2p_invite persistent=<Network ID> peer=<DUT#2_MAC_ADDRESS>		
	p2p_find		Make <b>DUT #1</b> keep in find phase with no time limit
		p2p_invite persistent=<Network ID> peer=<DUT#1_MAC_ADDRESS>	

## DUT\_1\_case\_6

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:6e

```
[root]# ./wpa_cli -i wlan0 list_networks
```

network id / ssid / bssid / flags

1 DIRECT-Yj 00:e0:4c:02:80:45 [DISABLED][P2P-PERSISTENT]

```
[root]# ./wpa_cli -i wlan0 p2p_invite persistent=1 peer=00:e0:4c:02:80:6e
```

P2P-INVITATION-RESULT status=1

```
[root]# ./wpa_cli -i wlan0 p2p_find
```

OK

P2P-INVITATION-ACCEPTED sa=02:e0:4c:08:90:20 persistent=1

## DUT\_2\_case\_6

```
[root]# ./wpa_cli -i wlan0 p2p_find 30
```

OK

```
[root]# ./wpa_cli -i wlan0 p2p_peers
```

00:e0:4c:02:80:45

```
[root]# ./wpa_cli -i wlan0 list_networks
```

network id / ssid / bssid / flags

1 DIRECT-Yj 00:e0:4c:02:80:45 [DISABLED][P2P-PERSISTENT]

P2P-INVITATION-RECEIVED sa=00:e0:4c:02:80:45 persistent=1

```
[root]# ./wpa_cli -i wlan0 p2p_invite persistent=1 peer=00:e0:4c:02:80:45
```

P2P-INVITATION-RESULT status=0 00:e0:4c:02:80:45

## (7) Improve the success rate of P2P nego to be GO

To improve the success rate to be P2P GO, we have to set the go\_intent as 14 and set the tie breaker bit. Please follow the low steps.

First, in source code, p2p\_connect function. (./src/p2p/p2p.c)

You need patch the red words before the return as below:

```
int p2p_connect(struct p2p_data *p2p, const u8 *peer_addr,
...
{
    ...
    dev->tie_breaker = 1;
    return p2p_connect_send(p2p, dev);
}
```

Second, in configure file for P2P, you need add this setting for default value

```
p2p_go_intent=14
```

Finally, in connect flow. Maybe the p2p\_connect with the go\_intent=14 parameter to overridden the default intent.

```
wpa_cli > p2p_connect <peer device address> pbc go_intent=14
```

If you can not control the go intent by command or configure. You can write the source code, wpas\_p2p\_connect function (./wpasupplicant/p2p\_supplicant.c)

You need patch the red words before the return as below:

```
int wpas_p2p_connect(struct wpas_supplicant *wpas, const u8 *peer_addr,
...
{
    ...
    if (go_intent < 0)
        go_intent = wpas->conf->p2p_go_intent;
    go_intent = 14;
    ...
}
```