

Wireless G Access Point

For Home/SOHO

- Up to 54Mbps Wireless Speed
- Advanced WPA/WPA2 Security
- Functions as Access Point or Wireless Repeater
- Easy Web-Based Management

FEATURES

- **802.11g WLAN Standard**
- **Up to 54Mbps Data Transfer Rate**
- **64/128-bit WEP Data Encryption**
- **WPA/WPA2 Personal and Enterprise Security With TKIP and AES Support**
- **Can be Configured to Operate in AP or Repeater Mode**
- **Wireless Connection to Ethernet Network/Servers**
- **Through 10/100BASE-TX Port**
- **Web-Based Configuration & Management**
- **System Log**

* Maximum wireless signal rate based on standard 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors lower actual data throughput rate.

AirPlus G



The AirPlus G DWL-G700AP is an 802.11g standard high-speed wireless access point designed for cost-effective home and small office wireless connection. This device features the latest advanced wireless silicon chip technology with enhanced security to shield and protect wireless communication from intruders.

802.11g Wireless Standard. Complying with the 802.11g WLAN standard, the DWL-G700AP provides speeds of up to 54Mbps when used with other 802.11g wireless products. Delivering throughput capable of handling heavy data payloads, this device is an ideal solution for bandwidth intensive applications. It is backward compatible with 802.11b wireless devices and provides seamless interoperability with the earlier standard equipment.

Multiple Operation Modes. The DWL-G700AP can be configured to operate in the AP or Repeater mode. In the AP mode, it acts as a base station, providing connectivity for the wireless computers. In the repeater mode, the DWL-G700AP can increase the wireless signal range of a wireless router or another access point deployed in the same network. This operation mode is useful in large homes and buildings. The DWL-G700AP takes existing wireless signals and repeats them to enable wireless connectivity in the basement, patio, garage or any "dead spot" areas where the original wireless signal could not reach.

Advanced Network Security. The DWL-G700AP supports 64/128-bit WEP data encryption and WPA/WPA2 security functions. For WPA with TKIP (Temporal Key Integrity Protocol) encryption, the DWL-G700AP supports personal (PSK) security when operating in the AP or Repeater mode, and enterprise (EAP) security when operating in the AP mode. For advanced WPA2 with AES (Advanced Encryption Standard) for authentication of 802.11 clients using server-side digital certificates, the DWL-G700AP supports PSK personal security in the AP and Repeater modes, and EAP enterprise security in the AP mode. In addition to WEP and WPA/WPA2, the DWL-G700AP also provides MAC Address Filtering to control user access, and the Disable SSID Broadcast function to limit outsiders' access to the internal network.



Product Specifications

Network Standards

- 802.11g wireless LAN
- 802.11b wireless LAN
- 802.3/802.3u 10BASE-T/100BASE-TX Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Media Access Control Protocol

CSMA/CA with ACK

Network Architecture Type

Infra-structure mode

Operating Frequency

2.4 to 2.4835 Ghz ISM band

Operating Channels

- FCC: 11
- ETSI: 13

Radio and Modulation Schemes

DQPSK, DBPSK, CCK, OFDM

Operation Modes

- AP
- Repeater

Receive Sensitivity (for 802.11b)

- (at 8% PER)
- 80dBm at 11Mbps
 - 84dBm at 5.5Mbps
 - 87dBm at 2Mbps
 - 88dBm at 1Mbps

Receive Sensitivity (for 802.11g)

- (at 10% PER)
- 82dBm at 6Mbps
 - 81dBm at 9Mbps
 - 79dBm at 12Mbps
 - 77dBm at 18Mbps
 - 74dBm at 24Mbps
 - 70dBm at 36Mbps
 - 66dBm at 48Mbps
 - 65dBm at 54Mbps

Transmit Output Power (for 802.11b)

16dBm typically

Transmit Output Power (for 802.11g)

13dBm typically

Security

- 64/128-bit WEP data encryption
- WPA-PSK, WPA2-PSK
- WPA-EAP, WPA2-EAP (AP mode only)
- TKIP, AES
- MAC address filtering
- SSID broadcast disable function

Antenna

2dBi Gain detachable omni-directional antenna with RP-SMA connector

Device Management

Web-based management through Internet Explorer v.6 or later, Netscape Navigator v.6 or later or other Java-enabled browser

Physical & Environmental

Diagnostic LEDs

- Power
- WLAN
- LAN

Operating Voltage

7.5VDC 1A

Power Input

Through external power adapter

Dimensions

142 (L) x 109 (W) x 31 (H) mm
(5.59 x 4.29 x 1.22 inches)

Weight

200 grams (0.44 lb)

Operating Temperature

0° to 55°C

Storage Temperature

-10° to 70°C

Operating Humidity

10% to 90% non-condensing

Storage Humidity

5% to 95% non-condensing

Certification

- FCC Class B
- CE
- C-Tick
- Wi-Fi



D-Link Worldwide Offices

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
France	TEL: 33-1-30238688	FAX: 33-1-30238689	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	India	TEL: 91-022-26526696	FAX: 91-022-26528914
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Portugal	TEL: 351-21-8688493		Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099 #350
Czech Republic	TEL: 420-(603)-276-589		Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-8168
			Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898