D-Link

DU-H4L

4-Port USB Hub

Cost-Effectively Connecting Your USB Devices

The DU-H4L 4-Port USB mini hub is designed to provide a simple, cost-effective USB 1.1 solution connection for your USB peripherals. The USB connection technology enables many interactive multi-media applications such as audio/video peripheral and collaborative computing. USB connections are made possible using USB standard cable.

Expanding Your PC or iMac
This 4-port USB mini hub allows you to connect up to 4 USB peripherals or devices to your USB ready PC or iMac. This hub provides an out-of-the-box industry-standard USB bus for PC and iMac users to expand the number of USB ports available on their systems.

Seamless Connections
The DU-H4L is designed to provide quick and easy access to the 4 type "A" downstream ports for connecting peripherals with USB support, other USB hubs and devices. A USB cable (Type"A") upstream port is provided for connecting to the host computer, or to another USB hub. Configured directly by the operating system, the DU-H4L operates seamlessly with both Microsoft's Open HCI and Intel's Universal HCI.

Low and High Speeds Support with Data Buffering
As a standard USB hub, the DU-H4L buffers USB data from any attached peripherals or devices in compliance with USB specification version 1.1 to provide an invisible extension of the USB bus. Supporting both low-speed 1.5 Mbps devices and fill-speed 12 Mbps devices, each port creates a bridge between the peripheral and the host computer.

No External Power Adapter Required
Power for the DU-H4L is provided directly from the USB bus for connection of up to 4 USB peripherals devices. You do not need any external power adapter to connect the hub to an external power source.

Features

- *USB 1.1 standard*
- *4 Type A ports to connect to 4 USB devices*
- *1 Type A Cable to connect to computer or another USB hub*

- *Pocket-sized, lightweight*
- *Diagnostic LEDs provided*
- *No external power adapter required*

DU-H4L

Technical Specifications

Standards
- USB Specification version 1.1
- OHCI
- UHCI

Supplied Current
4 ports support total 500mA from downstream port of USB host or upper level hub

Number of Ports
- 1 upstream USB port (USB Type A cable)
- 4 downstream USB ports (USB Type A connector)

Wiring Topology
Tiered Star

Connectivity Rules
- 5 cascaded hubs maximum
- 5 m maximum between each hub
- Up to 127 devices

Physical & Environmental

Dimensions
80.9 mm x 52 mm x 28 mm (device only)

Weight
115 gram (device only)

O.S. Support
- Windows 98, 98SE, ME, 2000, XP
- MacOS 8.9 and above

EMI Certifications
- FCC Class B
- CE Class B
- C-Tick

Box Includes
- DU-H4L mini Hub
- Installation Guide

CE FC FEDERAL COMMUNICATION COMMISSION U.S.A ACN 052 202 838

Ordering Information

DU-H4L	4-port USB 1.1 hub

D-Link®

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX:90-212-335-2500
Chile	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299

RECYCLABLE